



## Product Description

### FR1256

Recessed Downlight luminaire , Die-cast Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . Designed and equipped with uniform light distribution PMMA lens.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.




嵌入式筒灯，选用压铸式铝合金外壳，采用先进的粉末喷涂技术，有效提高抗氧化性和防腐性。

### FC1014

Surface Mounted Downlight luminaire , Die-cast Aluminum Alloy Housing with advance powder spray technology , anti-oxidation and anti-corrosion . Designed and equipped with uniform light distribution PMMA lens.

Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

明装筒灯，选用压铸式铝合金外壳，采用先进的粉末喷涂技术，有效提高抗氧化性和防腐性。



<b>Product Name/产品名称</b>	FR1256	FC1014
<b>Dimension/尺寸</b>	ø 36mm*34mm	ø 58mm*18mm
<b>Lamp Source/光源</b>	CREE COB (Bridgelux / CITIZEN Optional)	CREE COB (Bridgelux / CITIZEN Optional)
<b>Wattage/瓦数</b>	1.3W	3W
<b>Luminous Flux/光通量</b>	80 Lumen	230 Lumen
<b>Luminaire Efficacy/光效</b>	61 Lumen / Watt	76 Lumen / Watt
<b>Color Temperature/色温</b>	2700K, 3000K, 4000K, 5000K	2700K, 3000K, 4000K, 5000K
<b>CRI/显色指数</b>	>80 (90 Optional)	>80 (over 90 optional)
<b>Dimming Method/调光方式</b>	Triac, 0-10V, Dali	Triac, 0-10V, Dali
<b>Beam Angle/光束角</b>	20°	15° / 24°
<b>Cut Hole Size/开孔尺寸</b>	ø 30mm	/
<b>Available Color/外壳颜色</b>	White, Black	White, Black
<b>IP Rating/防护等级</b>	IP20	IP20
<b>Certification/证书</b>	CE	CE

# FR1256/FC1014