



Beam Angle (Full): 109°		
0.5	1.33	4883
1.0	2.66	1722
1.5	4.00	543
2.0	5.33	306
2.5	6.66	198
3.0	7.99	138

(CUSTOM MADE)

Product Description

High Lumen pendant luminaire with integrated LED linear light. Installation can be by hanged wires, optional accessories include wires and connecting plastic parts.



Applications: For star-rated hotels, restaurants, bars, boutiques, clubs, entertainment places, exhibition centers, museums, offices, opera houses, stores, homes, villas, etc.

高流明吊灯。安装可以通过吊线，可选配件包括电线和连接塑料部件。

CUSTOM MADE/定制：

90 Degree Modules for Modular system and or Individual Luminaire.

SKN4265用90度转角拼接模组。



| SKN7290

Product Name/产品名称	SKN7290				
Dimension(WxH)/尺寸	72mm x 90mm				
Dimension(L)/尺寸	0.6m	0.9m	1.2m	1.5m	1.8m
Lamp Source/光源	LED				
Wattage/瓦数	20W	30W	40W	50W	60W
Luminous Flux/光通量	1900 Lumen	2850 Lumen	3800 Lumen	4750 Lumen	5700 Lumen
Luminaire Efficacy/光效	95 Lumen / Watt				
Color Temperature/色温	3000K/4000K/6000K				
CRI/显色指数	>82				
Dimming Method/调光方式	Triac, 0-10V, Dali				
Beam Angle/光束角	110°				
Available Color/外壳颜色	Oxidized Silver / White Powder Spray as Default				
Shell Material/外壳材质	Aluminum+Matted Polycarbonate				
IP Rating/防护等级	IP20				