



Name: T8 Batten			Name: T5 Batten		
0.5	1.24	2269	0.5	1.38	1960
1.0	2.46	1867	1.0	2.75	1900
1.5	3.69	2520	1.5	4.13	2180
2.0	4.92	1420	2.0	5.51	1220
2.5	6.15	910	2.5	6.88	780
3.0	7.38	630	3.0	8.26	540
Distance (ft)	Core Diameter (mm)	Beamwidth (ft)	Distance (ft)	Core Diameter (mm)	Beamwidth (ft)

T8/T5 BATTEN

Product Description

T8 Batten

Metal sheet with white Powder coated simple Batten. Designed fully fit with new developed Miron LED Universal Tubes.

金属板与白色粉末涂层组合的T8支架。=适合新Miron LED通用管。

T5 Batten

A fully new developed LED Universal Tubes Retrofit for both electro magnetic and electronic Ballast.

全新开发的LED通用管改造，兼容传统镇流器。

Product Name/产品名称	T8 Batten	T5 Batten
Dimension/尺寸	1230x40x25mm	1175x60x85mm
Lamp Source/光源	LED	LED
Wattage/瓦数	18W (Miron tube)	14W (Miron Tubes)
Luminous Flux/光通量	2250 Lumen	1950 Lumen
Luminaire Efficacy/光效	125 Lumen / Watt	139 Lumen / Watt
Color Temperature/色温	2700K, 3000K, 4000K, 5000K	2700K, 3000K, 4000K, 5000K
CRI/显色指数	>82	>82
Dimming Method/调光方式	Triac, 0-10V, Dali	Triac, 0-10V, Dali
Beam Angle/光束角	300°	300°
Available Color/外壳颜色	Milky White	Milky White
IP Rating/防护等级	IP20	IP20
Certification/证书	CE, EN 60598-2-1, EN 60598-1, EN 62471, EN 62493, EN IEC 62031	CE